
REAL EASE BOO RE 800

REAL EASE 800, an effective chemical release agent for all types of concrete formworks.



General Description

The reduction of alkalis in water of the concrete with the applied release agent on the form will create a thin film which prevents any bond developing between the concrete and formwork thus enabling the formwork to be stripped easily.

Prevent excessive build-ups or puddles as it may cause retardation of concrete on the area.

Should spillage occur on the reinforcement, the contaminated area is to be removed by using a cloth or rag dampened with turpentine or coat it with cement slurry to react with the release agent and this slurry should brush off prior to concrete pouring.

Recommended For

REAL EASE 800 is suitable for all type of formwork and other areas where concrete build-ups or rusting is undesired.

Advantages / Benefits

- Prevent rusting of metal form
- Facilitates easy removal of formwork
- Ensuring longer life span of timber form
- No stain or discoloration to the concrete surface
- Will not affect the bonding of tiles, render or paint to be applied later
- Reduces the incidence of air pockets and tendency for surface spalling at corners

Recommended Dosage

REAL EASE 800 is a very economical version of form oil. No dilution necessary. Use as supplied.

Non-absorbent forms approximately 20m² per litre Porous or rough-sawn timber approximately 8m² per litre Smooth plywood or dense-grained timber approximately 12m² per litre

Clean all surface prior to application of **REAL EASE 800**. Apply thinly and evenly using spray, mop or rollers brush to get better efficiency.

Packaging

REAL EASE 800 supplied in 5 litres, 20 litres pail and sealed 205 litres drum.

Storage / Shelf Life

REAL EASE 800 can be stored for 1 year in tightly sealed original drum or pail.

Health and Safety Precaution

Inhalation

In case of discomfort, move to a ventilated area.

Skin Contact

Flush skin thoroughly with water.

Eve Contact

Flush eyes with water and carefully rinse under eyelids. If irritation persists, consult a physician.

Ingestion

Immediately rinse mouth with water. Do not induce vomiting. If conditions worsen, consult a physician immediately.



STATEMENT OF RESPONSIBILITY

The technical information and application advice given above are based on the present state of our best scientific and practical knowledge. As the information above is of a general nature, no assumption can be made as to the suitability of the product for a particular application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of the product for their intended use.

Field service where provided, does not constitute supervisory responsibility. The owner, engineer or contractor may reject or modify any suggestions made by REAL POINT SDN BHD either orally or in writing since ultimately it is their responsibility and not REAL POINT SDN BHD for carrying out procedures appropriate to a specific application.

REAL POINT SDN BHD (412492-U)

Corporate Office:

No.2, Jalan Intan, Phase NU3A1, Nilai Utama Enterprise Park, 71800 Nilai, Negeri Sembilan Darul Khusus.

Tel: 606 - 797 1633
Fax: 606 - 799 6833
Website: www.realpoint.com.my
Email: info@realpoint.com.my / sales@realpoint.com.my

Kota Kinabalu:

Lot 15, Lok Kawi Industrial Estate, Phase II, KM 19, Jalan Penampang-Papar Lama, 89600 Kinarut, Kota Kinabalu, Sabah.

Tel: 6088 - 750 622 / 751 622 Fax: 6088 - 752 622

Penang

No.38-0, Ground Floor, Lorong Tangling Indah 3, Taman Tangling Indah, Simpang Ampat, 14100 Simpang Ampat, Pulau Pinano.

Joho

Tel / Fax: 6082 - 433 230

No.371, Jalan Idaman 3/9, Kawasan Perindustrian Desa Idaman. 81400 Senai. Johor Darul Takzim.

Phase 2 (SMI Industrial Park), Jalan Bako, 93050 Kuching,

Lot 1479, (Sublot 156), Demak Laut Industrial Park,